

Tabuľka tolerančných pásiem pri 1mA

Obj. č. typu výrobku	TYP	Napätové tolerančné pásmo pre účely revízie typov výrobkov			
		spodná hranica (V _{dc})	horná hranica (V _{dc})		
81.001	PO I 1 280V/12,5kA	387	473		
81.002	PO I 2 280V/12,5kA				
81.003	PO I 3 280V/12,5kA				
81.004	PO I 4 280V/12,5kA				
81.005	PO I 1 R 280V/12,5kA				
81.006	PO I 2 R 280V/12,5kA				
81.007	PO I 3 R 280V/12,5kA				
81.008	PO I 4 R 280V/12,5kA				
81.023	PO I 1 EWS 280V/12,5kA				
81.024	PO I 2 EWS 280V/12,5kA				
81.013	PO I 3 EWS 280V/12,5kA				
81.014	PO I 4 EWS 280V/12,5kA				
81.025	PO I 1 R EWS 280V/12,5kA				
81.026	PO I 2 R EWS 280V/12,5kA				
81.015	PO I 3 R EWS 280V/12,5kA				
81.016	PO I 4 R EWS 280V/12,5kA				
81.009	PO I 1+1 280V/12,5kA				
81.011	PO I 1+1 R 280V/12,5kA				
81.027	PO I 3+1m 280V/12,5kA				
81.028	PO I 3+1m R 280V/12,5kA				
81.029	PO I 3+1m EWS 280V/12,5kA				
81.030	PO I 3+1m R EWS 280V/12,5kA				
81.031	PO I 1+1m 280V/12,5kA				
81.032	PO I 1+1m R 280V/12,5kA				
82.021	PO II 1 75V/40kA			108	132
82.022	PO II 2 75V/40kA				
82.023	PO II 1 R 75V/40kA				
82.024	PO II 2 R 75V/40kA				
82.056	PO II 0 75V/40kA				
82.025	PO II 1 130V/40kA			184,5	225,5
82.026	PO II 2 130V/40kA				
82.027	PO II 3 130V/40kA				
82.028	PO II 4 130V/40kA				
82.029	PO II 1 R 130V/40kA				
82.030	PO II 2 R 130V/40kA				
82.031	PO II 3 R 130V/40kA				
82.032	PO II 4 R 130V/40kA				
82.001	PO II 1 280V/40kA	387	473		
82.002	PO II 2 280V/40kA				
82.003	PO II 3 280V/40kA				
82.004	PO II 4 280V/40kA				
82.005	PO II 1 R 280V/40kA				
82.006	PO II 2 R 280V/40kA				
82.007	PO II 3 R 280V/40kA				
82.008	PO II 4 R 280V/40kA				
82.068	PO II 1 EWS 280V/40kA				
82.069	PO II 2 EWS 280V/40kA				

Tabuľka tolerančných pásiem pri 1mA

Obj. č. typu výrobku	TYP	Napätové tolerančné pásmo pre účely revízie typov výrobkov	
		spodná hranica (V _{dc})	horná hranica (V _{dc})
82.013	PO II 3 EWS 280V/40kA	387	473
82.014	PO II 4 EWS 280V/40kA		
82.070	PO II 1 R EWS 280V/40kA		
82.071	PO II 2 R EWS 280V/40kA		
82.015	PO II 3 R EWS 280V/40kA		
82.016	PO II 4 R EWS 280V/40kA		
82.017	PO II 1+1 280V/40kA		
82.062	PO II 2+1 280V/40kA		
82.018	PO II 3+1 280V/40kA		
82.019	PO II 1+1 R 280V/40kA		
82.063	PO II 2+1 R 280V/40kA		
82.020	PO II 3+1 R 280V/40kA		
82.033	PO II 1 385V/40kA	558	682
82.034	PO II 2 385V/40kA		
82.035	PO II 3 385V/40kA		
82.036	PO II 4 385V/40kA		
82.037	PO II 1 R 385V/40kA		
82.038	PO II 2 R 385V/40kA		
82.039	PO II 3 R 385V/40kA		
82.040	PO II 4 R 385V/40kA		
82.041	PO II 3+1 385V/40kA		
82.042	PO II 3+1 R 385V/40kA		
82.043	PO II 1 550V/40kA	819	1001
82.044	PO II 2 550V/40kA		
82.045	PO II 3 550V/40kA		
82.046	PO II 4 550V/40kA		
82.047	PO II 1 R 550V/40kA		
82.048	PO II 2 R 550V/40kA		
82.049	PO II 3 R 550V/40kA		
82.050	PO II 4 R 550V/40kA		
82.051	PO II 2+1 550V/40kA		
82.052	PO II 2+1 R 550V/40kA		
82.088	PO II 1 750V/30kA	1080	1320
82.089	PO II 2 750V/30kA		
82.090	PO II 3 750V/30kA		
82.091	PO II 4 750V/30kA		
82.092	PO II 1 R 750V/30kA		
82.093	PO II 2 R 750V/30kA		
82.094	PO II 3 R 750V/30kA		
82.095	PO II 4 R 750V/30kA		
82.096	PO II 2+1 750V/30kA		
82.097	PO II 3+1 750V/30kA		
82.098	PO II 2+1 R 750V/30kA		
82.099	PO II 3+1 R 750V/30kA		

Pozn.: Výrobky, ktoré majú v názve "+1" a "+1m", obsahujú bleskoistku. Moduly s bleskoistkou sa uvádzanými napätiami netestujú!

Tabuľka tolerančných pásiem pri 1mA

Obj. č. typu výrobku	TYP	Napäťové tolerančné pásmo pre účely revízie typov výrobkov	
		spodná hranica (V _{DC})	horná hranica (V _{DC})
81.250	POm I 280V/25kA	387	473
81.255	POm I R 280V/25kA		
81.261	POm I 1+1 280V/25kA		
81.262	POm I 1+1 R 280V/25kA		
81.253	POm I 3 280V/25kA		
81.257	POm I 3 R 280V/25kA		
81.259	POm I 3+1 280V/25kA		
81.260	POm I 3+1 R 280V/25kA		
81.254	POm I 4 280V/25kA		
81.258	POm I 4 R 280V/25kA		

Pozn.: Výrobky, ktoré majú v názve "+1" a "+1m", obsahujú bleskoistku. Moduly s bleskoistkou sa uvádzanými napätiami netestujú!